

## TEMPORARY REVISION

### OM-TR-MDC-E4-359b Supersedes OM-TR-MDC-E4-359

### EECU Software VC33\_xP\_05\_19

This Temporary Revision OM-TR-MDC-E4-359b is approved in conjunction with the Design Change Advisory MDC-E4-359b and is valid in conjunction with the latest revision of the Operation Manual (OM) until this Temporary Revision has been incorporated into the OM.

The limitations and information contained herein either supplement or, in the case of conflict, override those in the OM.

The technical information contained in this document has been approved by EASA.

Doc. Nr.	Affected Section(S)	Affected Page(s)
E4.01.02	4	4a
	5	2a
	7	1a

**Instruction:**

- Print this document on yellow paper (single-sided)
- Insert this cover page as the first page of the OM
- Insert the other pages of this Temporary Revision adjacent to or in front of the corresponding OM pages

## 4. Operating Instructions

### 4.3 Restart in flight

*The following chapter and its content are removed:*

#### ~~4.3.1 Restart of engine by windmilling~~

*The numbering is changed as follows:*

#### 4.3.1 Restart of engine by starter

*The existing list is replaced by the following:*

- Max. demonstrated altitude for immediate restart by starter: 15.000ft
- Max. demonstrated altitude for restart after 10 min. and ambient air temperature higher than ISA by starter: 10.000ft
- Max. demonstrated altitude for restart after 5 min. and ambient air temperature between ISA and ISA minus 10 °C by starter: 10.000ft
- Max. demonstrated altitude for restart after 2 min. and ambient air temperature below ISA minus 10 °C by starter: 10.000ft
- Airspeed: see applicable Aircraft Flight Manual
- Power Levers – “IDLE”
- Engine Master – “ON”
- Engage starter of engine (Key).

## 5. Emergency Procedures

*The following chapter is added:*

### 5.10 Restart of engine by windmilling

- Max. demonstrated altitude for immediate restart by windmilling: 15.000ft
- Max. demonstrated altitude for restart after 10 min. and ambient air temperature higher than ISA by windmilling: 10.000ft
- Max. demonstrated altitude for restart after 5 min. and ambient air temperature between ISA and ISA minus 10 °C by windmilling: 10.000ft
- Max. demonstrated altitude for restart after 2 min. and ambient air temperature below ISA minus 10 °C by windmilling: 10.000ft
- Airspeed: see applicable Aircraft Flight Manual
- Power Levers – “IDLE”
- Engine Master – “ON”.

## 7. Additional Information

### 7.1 Propeller Self Test (Automatic Run-Up Test)

*The existing list is replaced by the following:*



- Aircraft on the ground.
- Prop speed = idle (below 1150rpm).
- Power lever = idle (below 5% power lever position).
- No errors pending.
- Self test button active (and pressed during the whole test run).
- Gearbox oil temperature above 35°C